



## Description

The FORTA<sup>®</sup> Rover volumetric fiber dispenser is a variable speed, chop-on-demand dispenser of MOBILE-MESH™ fiber roving for addition into a volumetric concrete truck. Standard cut length of the roving is approximately 3/4 in. The Rover is very efficient and easy to operate.

The Rover is installed on the rear of the volumetric truck. It uses the truck's existing air supply and is easily connected to the truck's controls for convenient operation. The Rover chops the MOBILE-MESH™ roving at the desired feed rate and dispenses it directly onto the belt or into the mixing chamber of the truck.

## Advantages

- Exceptional accuracy
- Better quality control
- Low maintenance\*
- Easy to use
- Easy to install
- High capacity
- Easy to load and use

\* To maintain accuracy, some maintenance is necessary.

## Specifications

<b>Dimensions (H x W x D)</b>	19 x 12 x 12 in (485 x 305 x 305 mm)
<b>Weight</b>	32 lb (14.5 kg)
<b>Discharge Tube Diameter<sup>1</sup></b>	3 in (76.2 mm)
<b>Feed Rate (max)</b>	Approximately 2 lb/min (0.91 kg/min) <sup>2</sup>
<b>Weight of Bobbin</b>	42 lb (19 kg)
<b>Utilities Required for Operation</b>	
<b>Electrical</b>	12 or 24 VDC fused power source
<b>Air</b>	90 psi

1. Static-resistant tubing, length as needed to go between discharge on bottom of Rover and point-of-use on truck.
2. Feed rate of single bobbin unit. A two bobbin unit is available for increased yield.

*FORTA<sup>®</sup> Rover can be purchased from FORTA Corporation or an authorized FORTA<sup>®</sup> products distributor, dealer or representative.*

FORTA<sup>®</sup> and "Circles of Strength" mark are registered trademarks of FORTA Corporation  
© 2018 FORTA Corporation



## Applications

Used on volumetric concrete trucks for adding MOBILE-MESH™ alkali resistant glass fiber to concrete applications. Visit our YouTube channel to see our dispensers in action!



MOBILE-MESH™  
ROVING BOBBIN

## Warranty

FORTA<sup>®</sup> products are warranted to be free of defects in material and meet all quality control standards set by the manufacturer. FORTA Corporation specifically disclaims all other warranties, express or implied, and shall in no event be liable for any consequential, incidental or contingent damages of any type. The exclusive remedy for defective product or parts shall be to replace the product or parts, or refund the purchase price, at FORTA's sole discretion. No agent or employee of this company is authorized to vary the terms of this warranty notice.

FORTA reserves the right to change the features and specifications of its products without prior notice.